

ELO Home Series

ELO 200

Enable fast, efficient and smart EV charging option.

Its system is simple and featured with small footprint, convenient installation, and easy operation and offers up to 32 A charging. Easy to install and even easier to use. Simply plug in the 5m cable to your EV and start charging immediately.



Compatible with all electric vehicles.



2 Years Warranty



Open Charge Point Protocol (OCPP) 1.6 support.

Convenient & Stylish Design



- 4.3" Daylight color LCD touch screen with Charging status display.
- Dynamic LEDs show charging status.
- Multi language display : English & Thai.

Easy to Install & Use



- No matter what you drive or how much space is available in your electrical panel, EVLOMO ELO series fits right in.
- Quick-release mounting bracket & integrated cable management make set up & daily charging a breeze.
- 5m cable provides ease of use in garage or outdoor carport.
- Includes cable hanger bracket to keep the area tidy & clean.
- Includes emergency stop button.

Intelligent



- Control & monitor your electric charging.
- WiFi & 4G connectivity.
- Over-the-air firmware management & updates.
- Smartphone app for status updates & notifications.
- Usage & demand energy monitor.
- Real-time energy usage data evaluation.

Robust



- All-weather enclosure for indoor & outdoor use: IP65.
- Waterproof & weather designed, effectively block splashing water, rain, dust, snow, oil, UV, etc., can be widely used for both indoor & outdoor applications.
- Integrated RCD protection provides installation cost savings.

ELO 200



INPUT/ OUTPUT

Voltage	380/400/415 Vac
Phase	Three phase five wire: L1,L2,L3, N, PE
Current	32A
Capacity	22 kw
Frequency	50 ± 5 Hz
Noise	<55 dB

HUMAN MACHINE INTERACTION INTERFACE

LCD Screen	With
LED Indicator	Available
APP operation	Supported

CHARGING CONFIGURATION & STANDARD

No. of charging plugs	1
Charging cable length	5m
Charging protocols	Type2
Standards	IEC 62196, IEC 61851

TEMPERATURE & DIMENSIONS




Operating temperature	-20°C ~ +50°C
Storage temperature	-40°C ~ +80°C
Relative humidity	≤ 95%
Atmospheric pressure	70 ~ 106 kPa
Dimensions (W × D × H) (mm)	288.5×135×400 mm
Weight (kg)	≤ 20

EVLOMO Inc.,
1825 Corporate Blvd NW,
Suite 110, Boca Raton,
FL 33431 USA

EVLOMO TECHNOLOGIES CO., LTD
Raintree Office Garden 280 B2, Fl. 1ABC
Soi Soonvijai 4, Rama 9 Road, Huaykwang
Bangkok 10310, Thailand

EVLOMO™

Contact us:

-  Visit - www.evlo.com
-  Call - 02 000 9986 (Thailand)
 (561)878-5718 (USA)
-  Email - sales@evlo.com

EVLOMO, Inc. reserves the right to alter product offerings and specifications at any time without notice, and is not responsible for typographical or graphical errors that may appear in this document

Copyright © EVLOMO, Inc. All rights reserved. EVLOMO is a U.S. registered trademark/service mark of EVLOMO, Inc. All other products or services mentioned are the trademarks, service marks, registered trademarks, or registered service marks of their respective owners.